

Section 1: Identification

Product Name:**SUNCREME - HIGH LIFT BALAYAGE DEVELOPER 50 VOL 15%****Product Category:** Hair treatment

Section 2: Hazard Identification

**Warning****Danger****Skin Irritant Category 1****Serious Eye Damage Category 1****Specific Target Organ Toxicity Category 3 (Single Exposure)****GHS Precaution Phrases:**

H318: Causes serious eye damage

H314: Causes severe burn and eye damage

H335: May cause respiratory irritation

GHS Precautionary statements:

P102: Keep out of reach of children

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P233: Keep container tightly closed

P260: Do not breathe fumes/vapors

P264: Wash thoroughly after handling

P271: Use only outdoors or in a well ventilated area

P280: Wear protective gear. Face and eye protection, gloves and protective clothing.

GHS Response Phrases:

P301+330: If swallowed: Rinse mouth, do not induce vomiting

P303+351+361+363: If on skin or hair: Rinse skin with water or shower, take off immediately all contaminated clothing, wash contaminated clothing before use

P304+340: If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+310+351+338: If in eyes: Immediately call a poison center/doctor, rinse cautiously with water for several minutes, remove contact lenses, if present and easy to do. Continue rinsing

P405+403+235: Store locked up in a well ventilated space. Keep cool.

GHS Storage and Disposal Phrases:

P501: Dispose of contents/container to ... [... in accordance with local/regional/national/international regulation (to be specified)]

SAFETY DATA SHEET**SUNCREME - HIGH LIFT BALAYAGE DEVELOPER 50 VOL 15%****FS-00072****Created Date: 4/04/2019.****Section 3: Composition/Information on Ingredients**

INCI Name	Synonyms	CAS NUMBER	Conc. (%)
Aqua	Water	7732-18-5	70-100
Hydrogen Peroxide	-	7722-84-1	12
Cetyl Alcohol	-	36653-82-4	3-10
Cetearyl Alcohol	-	67762-27-0	1-3
Ceteareth-20	-	68439-49-6	1-3
Diethylenetriamine Pentamethylene Phosphonic Acid	-	15827-60-8	0.3-1
Paraffinum Liquidum	-	8042-47-5	0.3-1
Aloe Barbadensis Leaf Juice	-	85507-69-3/ 94349-62-9	0.1-0.3
Phosphoric Acid	-	7664-38-2	0.1-0.3
Acrylamide/Sodium Acrylate Copolymer	-	25085-02-3	<0.1
Trideceth-6	-	24968-91-8	<0.1

Note: Some Specific chemical Identities and/or exact percentage (Concentrations) have been withheld as a trade secret.

Section 4: First-Aid Measures**See Section 2****Emergency and First Aid Procedures**

1- Skin: Discontinue use of product. Apply cold compresses to affected areas to relieve any discomfort. If discomfort persists, you should contact a physician.

2 - Eyes: Immediately flush with clean, lukewarm water (low pressure) occasionally lifting eyelids. Seek medical attention if irritation develops.

3 - Inhalation: If respiratory irritation occurs, remove individual to fresh air. If person not breathing, contact emergency medical services, then give artificial respiration, preferably mouth to mouth if possible.

4 - Ingestion: Accidental ingestion of product may necessitate medical attention. In case of accidental ingestion dilute with fluids (milk or water). Do not induce vomiting. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed.

Hydrogen Peroxide irritates respiratory system and, if inhaled, may cause inflammation and pulmonary edema. The effects may not be immediate. Overexposure symptoms are coughing, giddiness and sore throat. In case of accidental ingestion, necrosis may result from mucous membrane burns (mouth, esophagus and stomach). Oxygen rapid release may cause stomach swelling and hemorrhaging, which may product major, or even fatal, injury to organs if a large amount has been ingested.

In case of skin contact, may cause burns, erythema, blisters or even necrosis.

Section 5: Fire-Fighting Measures

Extinguishing Media: Water, do not use any other media.

Fire Fighting Procedures: Contact emergency personnel. Use self-contained breathing apparatus and full protective gear, if large quantities of product are involved. Water runoff can cause environmental damage, dike and collect water used for fire fight.

Unusual Fire Fighting Procedures: Do not use straight streams of water.

Section 6: Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Do not inhale vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Vapors can accumulate in low areas.

Environmental precautions:

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains.

Methods for cleaning up: Eliminate all sources of ignition. A vapor suppressing foam may be used to reduce vapors. Do not touch or walk through spilled material. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations. Use clean non-sparking tools.

Section 7: Handling and Storage

Do not get on skin or in eyes. Do not inhale vapor or mist. Keep away from sources of ignition - No smoking. Open and handle container with care. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Use only in a well-ventilated area. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous.

Storage:

Keep container tightly closed in a cool, dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Consult local fire codes for additional storage information

Other Precautions: Avoid bacterial contamination. Keep containers tightly closed when not in use.

SAFETY DATA SHEET**SUNCREME - HIGH LIFT BALAYAGE DEVELOPER 50 VOL 15%****FS-00072****Created Date: 4/04/2019.****Section 8: Exposure Controls/Personal Protection****OSHA Permissible Exposure Limits**

Chemical Name	OSHA PEL	ACGIH TLV (TWA)
Hydrogen Peroxide (7722-84-1)	1 ppm	1 ppm

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equaled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Respiratory Protection: Avoid inhaling fumes

Skin Protection: Resistant Plastic or rubber gloves

Eye Protection: Safety glasses or goggles.

Section 9: Exposure Controls/Personal Protection

Appearance: Liquid Cream

Upper/lower flammability: N/A

Odor: Characteristic

Color: White

Vapor pressure: N/A

Odor threshold: N/A

Vapor density: N/A

pH: 2.3 to 3.0

Density (g/cm³): 0.900 to 1.100

Specific Gravity: 0.900 to 1.100

Melting point/freezing point: N/A

Solubility: Soluble in water

Initial boiling point and boiling range: >35 °C

Flash point: >115 °C

Evaporation rate: N/A

Flammability: N/A

Partition coefficient (n-octanol/water): N/A

Auto-ignition temperature: N/A

Decomposition temperature: N/A

Viscosity (cPs): 1,500 to 3,000

Note: Some of data above is not shown either because it is not relevant and/or readily available.

Section 10: Stability and Reactivity

Stability: Stable under normal conditions

Conditions to avoid: Direct Heat

Incompatibility (Materials to avoid): None

Hazardous Polymerization: Does not occur

Hazardous Decomposition Products: Unknown

Section 11: Toxicological Information

SAFETY DATA SHEET**SUNCREME - HIGH LIFT BALAYAGE DEVELOPER 50 VOL 15%****FS-00072****Created Date: 4/04/2019.**

NO INFORMATION

Section 12: Ecological Information

No ecological hazards have been tested to be associated with this product.

Section 13: Disposal Considerations

Do not contaminate food or feed by storage or disposal. Do not reuse empty container. Wrap empty container and throw in trash collection. Dispose of according to federal, state, and local regulations regarding health, air, and water pollution.

Section 14: Transport Information**DOT**

UN/ID no	2014
Proper Shipping Name	HYDROGEN PEROXIDE, AQUEOUS SOLUTION
Hazard class	5.1
Subsidiary class	8
Packing Group	II

TDG

UN/ID no	UN 2014
Proper Shipping Name	HYDROGEN PEROXIDE, AQUEOUS SOLUTION
Hazard class	5.1
Subsidiary class	8
Packing Group	II

ICAO/IATA

Air regulation permit shipment of Hydrogen Peroxide (<=40%) in non-vented containers for Air Cargo Only aircraft, as well as for Passenger and Cargo aircraft. HOWEVER, all PeroxyChem Hydrogen Peroxide containers are vented and therefore, air shipments of PeroxyChem H2O2 are not permitted. IATA air regulations state that venting of packages containing oxidizing substances is not permitted for air transport.

IMDG/IMO

UN/ID no	UN 2014
Proper Shipping Name	HYDROGEN PEROXIDE, AQUEOUS SOLUTION
Hazard class	5.1
Subsidiary Hazard Class	8
Packing Group	II

OTHER INFORMATION

Protect from physical damage. Keep drums in upright position. Drums should not be stacked in transit. Do not store drums on wooden pallets.

Section 15: Regulatory Information

No Information

Section 16: Other Information

██████████ believes that the information contained in this M.S.D.S is correct as of this date. However, because the material may be used under conditions which ██████████ has no control of or in ways we cannot anticipate, we give no warranty, expressed or implied, as to accuracy of the information and assume no responsibility for any damage to person, property or business arising from such use. Moreover, it is the responsibility of the purchaser or user of this material to ensure that is properly and safely used.

Created: 4/04/2019

Material Safety Data Sheet

MSDS Date: September 20, 2013

Page 1 of 5

1. Identification of the Substance/Preparation and the Company/Undertaking

Substance: SUNLIGHTS Professionnel Balayage Lightener

Unique reference Number: SUNLIGHTS 001

Company name & address: Sunlights Balayage, Inc.
3330 Piedmont Road
Suite 10
Atlanta, GA 30305
United States

Telephone: 1-(855)-820-7677

Fax: (404) 262-1115

Emergency Telephone Number: 1-(800)-535-5053
(International: 001-352-323-3500)

2. Composition

INCI	Range	CAS	EINECS	Classification	R/S Phrases
Ammonium Persulfate	1-10%	7727-54-0	231-786-5	O	R8
Potassium Persulfate	30-60%	7727-21-1	231-781-8	O	R8
Sodium Metasilicate	1-10%	6834-92-0	229-912-9	C, Xn	NA

*Remaining ingredients not listed. Proprietary blend.

3. Hazards Identification

Emergency Overview: OXIDIZER. HARMFUL IF SWALLOWED. IRRITANT TO EYES AND SKIN.

Route(s) of Entry:

- Eyes: Causes irritation, redness, and pain.
- Inhalation: Causes irritation to the respiratory tract. Symptoms may include coughing, shortness of breath.
- Ingestion: Seek medical attention.
- Skin: May cause irritation.

Signs and Symptoms of Exposure: Irritating to eyes.
May cause skin irritation.

Chronic Effects: Not determined

Most important hazards: Not determined

Specific hazards: Not determined

4. First aid measures

General Information: Some individuals may experience an allergic reaction to one or more of the components.
Immediately rinse any splashes on the skin and clothing.

Possible Exposures: Eyes, Skin, Accidental swallowing

Skin contact: Wash with soap and water for minimum of 15 minutes.

Eye contact: In case of accidental contact with the eye, wash out immediately with running water or eyewash solution for a minimum of 15 minutes, seek medical attention if irritation persists.

Ingestion: Seek medical attention.

Inhalation: Remove to fresh air, if symptoms develop, seek medical advice

Effects of over-exposure: Irritating to skin and mucous membranes of eyes and respiratory system.

5. Fire fighting measures

Material Safety Data Sheet

MSDS Date: September 20, 2013

Page 2 of 5

Suitable extinguishing media:

Use water spray to blanket fire, cool fire exposed containers, and to flush non-ignited spills or vapors away from fire. Do not allow water runoff to enter sewers or waterways.

Unsuitable extinguishing media:

Water

Special hazards in fire:

Not combustible, but substance is a strong oxidizer and its heat of reaction with reducing agents or combustibles may cause ignition. Contact with oxidizable substances may cause extremely violent combustion. Decomposes with liberation of oxygen which may intensify surrounding fire conditions. Burning may cause toxic fumes.

Required special protective equipment for fire-fighters:

Self-contained breathing apparatus

Additional Information:

Not determined

6. Accidental release measures

Personal precautions:

Follow recommendations for protection, avoid prolonged inhalation of dust

Environmental precautions:

Do not allow water runoff to enter sewers or waterways.

Methods for cleaning:

Remove all sources of ignition. Spilled material should be collected and put in approved DOT container and isolated for disposal. Isolated material should be monitored for signs of decomposition (fuming/smoking). If spilled material is wet, dissolve with a large quantity of water and dispose as a hazardous waste. All disposals should be carried out according to regulatory agencies procedures. Pick up spill for recovery or disposal and place in a closed container.

Waste disposal requirements:

Properly dispose of waste according to local, state, and federal environmental regulations.

Personal protective equipment required for clean up:

Wear protective gloves and goggles when cleaning up large spills. Impermeable clothing is recommended, to avoid contact with skin and clothing.

7. Handling and storage

Handling:

Avoid contact with eyes.

Do not eat, drink or smoke while handling the product.

Wear appropriate hand and eye protection

Use care to minimize dust generation in air.

Storage:

Keep out of reach of children

Store in a cool dry area

Store in original containers away from sources of heat and/or ignition.

Keep in a tightly closed container, ventilated area. Protect against physical damage. Isolate from incompatible substances. Separate from combustibles, organic or other readily oxidizable materials. Avoid storage on wood floors.

8. Exposure Controls

Occupational exposure controls:

The maximum occupational exposure limit will not be reached under normal conditions of use.

Engineering measures:

Good general ventilation is recommended.

OSHA Permissible

Exposure Level (PEL):

Ingredient	ACGIH	OSHA
Ammonium Persulfate	0.1 mg/m3 (TWA)	Not Established
Potassium Persulfate	0.1 mg/m3 (TWA)	Not Established
Sodium Metasilicate	2 mg/m3 (TWA)	Not Established

Material Safety Data Sheet

MSDS Date: September 20, 2013

Page 3 of 5

Personal protection equipment:	Glasses, gloves, dust mask
Respiratory:	None required. Use NIOSH approved dust mask if dust levels are irritating.
Eye protection:	Eye protection with side shields
Hand protection:	Wear chemically resistant protective gloves
Hygiene measures:	General hygiene practices for chemical products handling

9. Physical and chemical properties

Appearance:	Free Flowing Powder
Odor:	Bleach Odor
pH (1%):	9.0 – 11.5
Boiling point:	Not determined.
Melting point:	Not applicable
Flashpoint:	Not determined
Explosive properties:	Not determined
Vapour pressure:	Not applicable
Relative density:	>0.5
Solubility:	Soluble

10. Stability and reactivity

Conditions to avoid:	Unstable. Gradually decomposes losing oxygen. Decomposes more rapidly at higher temperatures. Metals other than stainless steel are apt to cause decomposition of persulfate solutions. Generates heat when mixed with acid. May react with ammonium salt solutions resulting in evolution of ammonia gas.
Materials to avoid:	Moisture, combustible material, heat, flame, ignition sources, shock, friction, powdered metals, phosphorus, hydrides, organic matter, halogens, acids, alkalis. and incompatibles.
Hazardous decomposition products:	Decomposed by moisture to form oxygen and ozone. Burning may produce nitrogen oxides, sulfur oxides, and sulfuric acid

11. Toxicological information

Excessive exposure may affect human health as follows:

Skin contact:	Irritant
Eye contact:	Irritant
Inhalation:	Irritant
Ingestion:	Treat symptomatically and supportively. Seek medical attention.
Medical conditions generally aggravated by exposure:	Some individuals may experience allergic reaction to cosmetic product.
Signs and symptoms of exposure:	In sensitive individuals, irritation and dermatitis may develop.

12. Ecological information

Not determined

13. Disposal Considerations

Material Safety Data Sheet

MSDS Date: September 20, 2013

Page 4 of 5

Dispose of in accordance with local, state and national waste disposal regulations. The bottle must be completely empty before disposal.

14. Transport information

US DOT 49 CFR:	Consumer Commodity, ORM-D
IATA Classification:	Oxidizing Solid, N.O.S. (Potassium Persulfate), Class 5.1, UN 1479, Packing Group No. III, Limited Quantities
Water (IMO) Classification:	Oxidizing Solid, N.O.S. (Potassium Persulfate), Class 5.1, UN 1479, Packing Group No. III, Limited Quantities

15. Regulatory information


Hazard Symbols



Xn Harmful



Xi Irritant



Oxidizer

R Phrases	R22	Harmful if swallowed.
	R36/38	Irritating to eyes and skin.
	R43	May cause sensitization by skin contact.
S Phrases	S20/21	When using do not eat, drink or smoke
	S24/25	Avoid contact with skin and eyes
	S26	In case of contact with eyes, rinse immediately and seek medical advice
	S37	Wear suitable gloves

US Federal Regulations:

TSCA (Toxic Substances Control Act) Status

All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

This product is regulated as a cosmetic product under EU Directive 76/768/EEC, and legislation in member states deriving from the directive.

As a cosmetic product, this material is exempt from UK's Chemicals (Hazard Information and Packaging for Supply) Regulations (CHIP) regulations. The CHIP regulations are the UK implementation of EU 67/548/EEC ("the substances Directive"), 1999/45/EC ("the preparations Directive"), and 76/769/EEC 91/155/EEC ("the safety data sheets Directive")

16. Other Information

When using this product follow the instructions and the safety precautions supplied with it.

The information and recommendations contained herein are presented in good faith, and, are believed to be correct. However, Sunlights Inc. assumes no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. In no event will Sunlights Inc. be responsible for damages of any nature whatsoever resulting from the use of or reliance upon this information.

Material Safety Data Sheet

MSDS Date: September 20, 2013

Page 5 of 5

Recipients of our products must take responsibility for observing existing laws and regulations.

Issue Date:	9-20-13
Issued By:	Sunlights Balayage, Inc.

Revision Level:	A
-----------------	---

SUNLIGHTS® *balayage* INC.

3330 Piedmont Rd., Suite 10
Atlanta, GA 30305 United States
1 (855) 820-7677

SAFETY DATA SHEET

The OSHA Hazard Communication Standard 29 CFR 1910.1200 requires that the information contained on this sheet be made available to your workers. Instruct your workers to handle this product properly.

Issued/Revised: March 2, 2015

SECTION I: IDENTIFICATION

PRODUCT: The Balay Wrap

SYNONYMS: Balayage Wrap or Film

CHEMICAL FAMILY: Polyolefins; Ethylene based polymers

FORMULA: Proprietary blend of resins

Unique Reference Number: SUNLIGHTS 002

Company name & Address: Sunlights Balayage, Inc.
3330 Piedmont Road, Suite 10
Atlanta, GA 30305
United States

Telephone: 1 (855) 820-7677

Fax: 1 (404) 262-1115

Emergency Telephone (Infotrac): 1 (800) 535-5053
International: 001-352-323-3500

SECTION II: INGREDIENTS

MAJOR COMPONENT: Polyethylene and/ or ethylene copolymers, and/ or propylene polymers and/ or butylene polymers

HAZARDOUS COMPONENTS: None

NFPA HAZARD ID: Health: 0 Flammability: 1 Reactivity: 0

SECTION III: TYPICAL PHYSICAL/CHEMICAL DATA

APPEARANCE: Clear plastic film

ODOR: None

SOLUBILITY IN WATER: None

SPECIFIC GRAVITY: .915 to .930

MELT TEMPERATURE: 225 F - 265 F

SUNLIGHTS® *balayage* INC.

3330 Piedmont Rd., Suite 10
Atlanta, GA 30305 United States
1 (855) 820-7677

SAFETY DATA SHEET

THE BALAY WRAP

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

GENERAL HAZARD: Solid material may burn at or above the autoignition temperature. If the film is thermally decomposed, flammable and/ or toxic gases may be released.

AUTOIGNITION: Over 500 F

EXTINGUISHING MEDIA: Water Spray, Dry chemical, Foam, Carbon Dioxide, Water Fog

SPECIAL FIRE FIGHTING PROCEDURES: For fires in enclosed areas, fire-fighters must wear positive pressure, self-contained breathing apparatus. Do not direct a solid stream of water or foam into burning molten plastic as this may cause spattering and spread fire.

UNUSUAL FIRE/EXPLOSION HAZARDS: None.

STATIC DISCHARGE: Plastic material can accumulate static charges.

SECTION V: HEALTH HAZARD DATA

INHALATION: None

INGESTION: None

SKIN: None at ambient temperature. Hot or molten plastic may cause thermal burns.

HEALTH HAZARDS (Acute and Chronic): None at ambient conditions.

EFFECTS OF OVEREXPOSURE: None

CARCINOGENICITY: None

OSHA REGULATED: No

EMERGENCY FIRST AID PROCEDURES: Inhalation of vapors from hot material - Remove to fresh air.
Dermal/Eye – For thermal burns, flush with large amounts of water, do not use ice.

SUNLIGHTS® *balayage* INC.
3330 Piedmont Rd., Suite 10
Atlanta, GA 30305 United States
1 (855) 820-7677

SAFETY DATA SHEET

THE BALAY WRAP

SECTION VI: REACTIVITY DATA

STABILITY: ☒ Stable ☐ Unstable

CONDITIONS TO AVOID: High temperatures - greater than 500 F, open flames, sparks and strong oxidizing substances.

INCOMPATIBILITY: Strong oxidizing agents, fluorine, some hydrocarbons cause softening.

HAZARDOUS COMBUSTION/DECOMPOSITION PRODUCTS: Thermal decomposition may produce carbon monoxide, aldehydes and other organic vapors.

Carbon monoxide is highly toxic if inhaled, carbon dioxide in high concentration can act as an asphyxiant, and some aldehydes can be irritants and/ or carcinogenic.

Local exhaust ventilation is recommended for airborne fumes and vapors.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VII: PRECAUTIONS FOR SAFE HANDLING AND USE

SPILLS: Not expected from this product.

WASTE DISPOSAL METHOD: Recycle; material should be packaged, labeled, transported and disposed of in accordance with local, state, and federal regulations.

ENVIRONMENTAL CONCERNS: Avoid discarding of plastic into surface waters.

SECTION VIII: SPECIAL PROTECTION INFORMATION AND CONTROL MEASURES

RESPIRATORY PROTECTION: Use NIOSH approved respirator if unable to control air-borne fumes or vapors.

VENTILATION: Local exhaust should be used over heating operations to control airborne fumes.

SPECIAL EXHAUST: None required under ordinary conditions of use, and with adequate ventilation.

SUNLIGHTS® *balayage* INC.

3330 Piedmont Rd., Suite 10
Atlanta, GA 30305 United States
1 (855) 820-7677

SAFETY DATA SHEET

THE BALAY WRAP

OTHER PROTECTIVE EQUIPMENT: Gloves and suitable eye protection that meet applicable ANSI standards.

SECTION IX: OTHER SPECIAL PRECAUTIONS

DO NOT STORE NEAR HEAT, OPEN FLAMES, OR STRONG OXIDIZING MATERIALS.

SECTION X: REGULATORY INFORMATION

SECTION XI: OTHER INFORMATION

In accordance with "Right to know" this product contains the following materials:

CAS #	Chemical Name
9002-88-4	Polyethylene Homopolymer and/ or
25087-34-7, 25213-02-9	Ethylene/Butene or Hexene Copolymer and/ or
9010-79-1	Polypropylene and/ or
9003-29-6	Polyisobutylene

Inventory Lists: TSCA

In accordance with SARA Title III, Section 313, this product contains the following chemicals subject to reporting: NONE

In accordance with SARA 302, 304, this product contains the following chemicals subject to reporting: NONE

CERCLA (Comprehensive Environmental Response, Compensation and Liability Act of 1980 Section 103). Because no constituents of the plastic film is released to the environment under normal conditions of use, it is not subject to reporting.

Most of the data contained herein was obtained from raw materials suppliers.

SUNLIGHTS® *balayage* INC.

3330 Piedmont Rd., Suite 10
Atlanta, GA 30305 United States
1 (855) 820-7677

DISCLAIMER

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANT ABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY Sunlights Balayage, Inc. except that the product shall conform to contracted specifications, and that the product does not infringe any valid United States Patent. The information provided herein was believed by Sunlights Balayage, Inc. to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of product and to determine the suitability of the product for its intended use. Buyer's exclusive remedy shall be for damages and no claim of any kind, whether as to product delivered or for non-delivery of product, and whether based on contract, breach of warranty, negligence or otherwise, shall be greater in amount than the purchase price of the quantity of the product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.

PREPARED BY: SUNLIGHTS BALAYAGE, INC.
3330 Piedmont Rd. Suite 10
Atlanta, GA 30305
United States